





POSMO II

15" and 17" POS Touch Monitor with MSR and SCR Integrated

The POSMO II is a compact touchscreen display developed to provide the most cost-effective solution available.

It saves valuable space at the cash wrap due to its small footprint. It offers an industrial grade LED LCD panel as standard features.

The POSMO II touch screen display is engineered to be highly versatile, durable, aesthetically pleasing and value priced, a winning combination.

- 15" LCD Display (1024 x 768, Resistive Touch)
- 17" LCD Display (1280 x 1024, Projective Capacitive Touch)
- Eco-friendly, Low Power LED Backlight Display
- Compact Space-Saving Design
- Optional Multi-reader (MSR, SCR, I-Button)

Slim & Compact Design

• Fit seamlessly into any store environment





Specifications

	POSMO II (15 inch)	POSMO II (17 inch)
Display Size / Type	15" LED Backlight TFT-LCD	17" LED Backlight TFT-LCD
Resolution	1024 x 768 Resolution	1280 x 1024 Resolution
Brightness	LCD panel : 250 cd/m ²	LCD panel : 250 cd/m²
Contrast ratio	500 : 1 (Typ.)	1000 : 1 (Typ.)
Touch Screen	5-wired Resistive Touch	Projected Capacitive Touch
Response time	8mm/sec	8mm/sec
Viewing Angle	80/80/80/80 (Typ.)	85/85/80/80 (Typ.)
Port & Connector	VGA x 1, USB A Type x 2, USB B Type x 1, Audio x 1, RJ45 x 1 (for MSR)	
MSR (Option)	Comply with ISO 7811, Support 1& 2 & 3 track	
Power	DC 12V / 3A	
Dimension (WxHxD)	364 x 345 x 217(mm), 14.3 x 13.5 x 8.5(inch)	392 x 376 x 217(mm), 15.4 x 14.8 x 8.5(inch)

Durable and Stable Stand LCD Display (Options)

- Cable management • Sturdy base design offers
- 15", 17" LED LCD
- Resistive or PCAP Touch



Multi-reader (Options)

- Magnetic Stripe Reader (MSR)
- Smart Card Reader (SCR)





*Specifications may change without prior notice.