

2 Inches Direct Thermal Label Printer (OCBP-006)

Features:

- Support thermal roll paper / adhesive paper
- The print head with adjustable pressure
- Automatic paper checking function
- Temperature adaptive control
- Modular design, to meet different application requirements
- label printing machine,barcode label thermal printer,direct thermal label printer



Specifications:

| | |
|--------------------------|---|
| Printing method | Direct thermal |
| Resolution | 203DPI |
| Print width | 20-60mm |
| Printing speed | MAX:127mm/s ; MIN:50.8mm/s |
| Memory | DRAM: 4M FLASH: 4M |
| Print head temperature | Thermistor |
| Paper exists detection | The micro switch |
| Interface | USB |
| Paper presence detection | Paper presence detection |
| Barcode | CODE128, EAN128, ITF, CODE39, CODE93, EAN13, EAN13+2, EAN13+5, EAN8, EAN8+2, EAN8+5, CODABAR, POSTNET, UPC-A, UPCA+2, UPCA+5, UPCE, UPCE+2, UPCE+5, CPOST, MSI, MSIC, PLESSEY, ITF14, EAN14 Qrcode, DM Code, PDF417 |
| Internal font | FONT 0 to FONT 8 |
| Enlargement & r | (0°、90°、270°、 360°) 1 to 10 times enlargement in both direction; 0°、90°、270°、 360° |

| | |
|---------------------|---|
| otation | rotation |
| Image | Monochromatic PCX, BMP image files can be load to FLASH, DRAM |
| Paper type | Paper roll, sticker, adhesive sticker, etc |
| Paper width | 20mm ~ 60mm |
| Roll external | MAX 80mm |
| Roll inner diameter | MIN 25mm |
| Paper off type | Tear off |
| Power supply input | DC12V, 3A |
| Weight | 1.04KG |
| Dimensions | 190(D) x 135(W) x 137(H)mm |
| Work environment | 5 ~ 45°C, 20 - 80%RH(no condensation) |
| Storage environment | - 40 ~ 55°C , ≤93%RH (40°C) |