

Technical Specifications

Casing	Robust industrial grade metal material
Drawer	Heavy duty ABS plastic trays with adjustable bill compartment
Bill tray	POS-423: 4 / 5 adjustable bill compartment, that fits all int'l currencies POS-523: 4 adjustable bill compartment, that fits all int'l currencies
Coin tray	8 coin compartments
Bill clip	Rigid Metal Bill Clips
Media Slot	1 Front access slot for check or receipt
Type of key-lock	3 station key-lock
Solenoid release mechanism	24V / 6 PIN, RJ11 printer interface
Drawer opener	Electromechanical or manual operation Pulse width : 100 to 200 milliseconds Pulse duty cycle : 10% MAX
Micro Switch	Standard, open by driver signal to the solenoid
Control Command	ECR/POS
Operating System	DOS, UCDOS, Linux, Windows 95, 98, NT, 2000, ME, XP, XPe, Vista, 7, 8
Dimensions	POS-423: 400(W) x 410(D) x 85mm (H) POS-523: 350(W) x 390(D) x 80mm (H)
Weight	POS-423: 6.0KGs POS-523: 4.6KGs

PIN-ASSIGNMENTS 6-Pin 24V

PIN # 1	White	Not connected
PIN # 2	Black	Solenoid -
PIN # 3	Red	Switch +
PIN # 4	Green	Solenoid +
PIN # 5	Yellow	Not Connected
PIN # 6	Blue	Switch -



Birch is a trademark of Birch Technology U.S.A. Inc
All other products, brands or companies are trademarks or registered trademarks of their respective companies.

Specifications are subject to change without prior notice

Contact us for details