



BP-525D

BP-525D Series

2" Paper Width Thermal direct label printer

5"/second speed, Serial and USB

Most Cost-Effective High Speed Direct Thermal Printer



- Retailing Stores (POS)
- Office Automation (O/A)
- Factory Automation (F/A)
- Hospital and Health Care
- Other Related Automation

Ordering Information:

BP-525D: 203 dpi thermal direct barcode printer, 2" paper width, 5"/second speed, serial and USB port

K-012A: Smart Keyboard Display Unit(KDU)

1. High-Performance thermal direct

BP-525D offers standard memory of 4MB Flash, 8MB SDRAM and a slot for MicroSD card slot that users can inexpensively expand the flash memory storage maximum to 4GB. Furthermore BP-525D built with Real time clock (RTC) and built-in 32 bit processor with a print speed up to 5"/second with 203 dpi resolutions.

2. Supports more interfaces

BP-525D supports 2-in-1 interface serial and USB 2.0 port to meet the PnP applications. Furthermore an-on-board internal Ethernet LAN interface is optional for easy integration into network system. Most specially, BP-525D offers the option of graphic LCD display to have more convenient operating.

3. Clamshell-design and Easy Repairs

BP-525D is a user-friendly " Clamshell: design which allows the user to have easy label loading/unloading. Top of the form sensing by gap, black mark or notch is standard and completely adjustable from side to side. Furthermore, BP-525D is specially design with wall mount hole at the bottom cover for those wall-mounting needed environment.

4. For most of applications

BP-525D has a special design for different sized label load. Label stored inside the printer can be up to a 5" OD on a 1" core. The compact and small foot print offers flexible space-saving placement and remarkable versatility.

5. Powerful programmable Language support and BarTender

BP-525D delivers powerful programmable language codepage which supports different printer languages on board, including Zebra and Eltron. BP-525D bundled BarTender software as our standard.



Multi-European Languages available (codepages)
Compact and powerful desktop label printer



Technical Specifications

•Printer

Printing Method: Direct Thermal Mechanism Printed

Density: 203dpi (8dots/mm)

Maximum Print Width: 54mm (2.13")

Maximum print length: 2,286mm (90")

Printing Speed: 50mm, 76mm, 100mm, 127mm (2, 3, 4, 5 ips)
50mm, 76mm, (2, 3 ips)
selectable with peel off function

•Enclosure

Material: Double-walled Plastic
Operation Panel: LED (3 colors, Error, On line, Clearing data and Downloading data), Power Switch, Feed button

Dimension: 209mm x 109mm x 171mm (8.23" x 4.29" x 6.73")

Label roll capacity: 127mm (5") OD, 1" core

Others: With wall mounting hole at the bottom cover

•Media

Media type: Continuous, die-cut, black mark, fan-fold, notch, wristband

Media wound type: Outside wound
Media width: 15~60mm (0.59"~2.36")

Media thickness: 0.06~0.19mm (2.37~7.4mil), max. 150g/m²

Media core diameter: 25.4~38mm (1"~1.5")

Label length: 10~2,286mm (0.39"~90")

Peel off mode: 25.4~152.4mm (1"~6")

Cutter mode: 25.4~2,286mm (1"~90")

•Hardware

Processor: 32-bit RISC CPU

Memory: 4MB FLASH memory, 8MB SDRAM, MicroSD card slot for memory expansion up to 4GB

Sensors:

■ Gap transmissive sensor (offset 4mm from center)

■ Moveable black mark reflective sensor

■ Head open sensor

Interface: RS-232 (max. 115,200bps) and USB 2.0 (full speed mode)

Optional for Internal Ethernet

Power: AC 100-240V, DC 24V 2A, external universal switching power supply

Operation switch, button: One power switch & feed button

Real time clock: Standard with RTC

Optional: Guillotine cutter for full cut or partial cut, peel off module and internal Ethernet card

•Software

Application Software: Bar Code Symbolologies

Windows Driver: For Windows 95, 98, NT4.0, 2000, XP.

Software: Bar Tender

•Firmware

Font Direction: 0, 90,180,270 degrees

Bar Code:

1D bar code : Code 39, Code 93, Code 128UCC, Code 128 subset A,B,C, Codabar, Interleave 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A

UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China Post, RSS-14, Code 11

2D bar code : PDF-417, Maxicode, DataMatrix, QR Code, Aztec

Fonts : 8 alpha-numeric bitmap fonts

One Monotype® Imaging CG Triumvirate Bold Condensed scalable font

Printer language: TSPL-EZ™

•Others

ReliabilityHead: 30 km

Environment

Operation: 5°C ~ 40°C

Storage: -40°C ~ 60°C

Safety: FCC Class B, CE Class B, C-Tick Class B, UL, CUL, TUV/GS, CCC

•Options:

■ Internal Ethernet interface (10/100 Mbps)

■ Peel off module

■ Guillotine cutter

Full cut: Paper thickness

0.06~0.19mm, 200,000 cuts

Partial cut: paper thickness 0.06~0.12mm, 500,000 cuts; paper thickness 0.19mm, 200,000 cuts

■ Bluetooth module (serial interface)

■ Graphic type LCD display (128 x 64 pixel with back light)



Paper

Thermal direct paper:

29 x 10mm	2,500 pcs/roll	10 rolls/pack
29 x 25mm	1,100 pcs/roll	10 rolls/pack
40 x 20mm	1,300 pcs/roll	8 rolls/pack
58 x 35mm	800 pcs/roll	5 rolls/pack

Thermal direct paper: We offer a series of the thermal direct paper.



Birch is a trademark of Birch Technology U.S.A. Inc
All other products, brands or companies are trademarks or registered trademarks of their respective companies.

Specifications are subject to change without prior notice

Contact us for details