

SuperLead

苏州斯普锐智能系统有限公司

7708

立式二维码扫描大平台 (百万像素)
Presentation Scanner (Megapixels)

超大扫描窗口
Large Field of View



硬朗设计风格
Rugged Design

- 物体自感应
- 内置RS232和USB接口
- 多国语言条码信息宣传
- Object self induction
- Build in RS232 and USB interface
- Read all Mainstream 1D/2D Barcodes

- 全面读取主流一维、二维码
- 快速读取手机屏幕条码
- 功耗低、性能强
- Low Power Consumption, Strong Performance
- Fast Mobile Phone Screen Barcode Reading
- Multiple Language Barcode Message Transfer

Physical Characteristics	
尺寸Dimensions:	152mm x 149mm x 80mm
重量Weight:	376g
电压Voltage:	5 VDC $\pm 10\%$
电流Current:	500mA (Operating) 800mA max
Performance Characteristics	
光源Light Source:	Illumination: 617nm RED LED
视场角Field of View:	38.5°(H)x32.5°(V)
偏转/倾斜/旋转Roll / Pitch / Yaw:	360°, $\pm 65^\circ$, $\pm 60^\circ$
打印对比度Print Contrast:	15% minimum reflective difference
可识别电子屏幕Screen Intensity :	30% 及以上
运动容差Motion Tolerances	up to 600 cm per second
接口支持Interfaces Supported:	USB, RS232
传感器像素Image (Pixels):	1280pixels (H)x1080pixels (V)
Symbology Decode Capability	
一维条码1-D:	UPC, EAN, Code128, Code 39, Code 93, Code11, Matrix 2 of 5, Interleaved 2 of 5, Codabar ,etc.
二维条码2-D:	PDF417, MicroPDF417, Data Matrix, Maxicode, QR Code, MicroQR, Aztec, etc.
条码精度Minimum Resolution	3 mil Code39
User Environment	
工作温度Operating Temperature:	0°C to 50°C
存储温度Storage Temperature:	-40°C to 70°C
湿度Humidity:	0% to 95% relative humidity,non-condensing
抗跌落 Drop Specifications:	Designed to withstand 0.3m(5') drops
环境光免疫Ambient Light Immunity:	100.000 Lux.
Decode Ranges	
3.9mil C39	5mm-30mm
5.13mil C39	0mm-100mm
6.88mil PDF	0mm-150mm
13mil UPC-A	0mm-220mm
20mil QR	0mm-240mm
Performance may be impacted by bar code quality and environmental conditions	
   	