


# LCD-50

## TFT-LCD Display

- 40 character(20×2 )/80 character(20×4 )  
Display More Information
- Characters/background colors can be changed freely
- Low power consumption  
LCD-50 is only 0.5W 
- LCD-50 : 24\*48/40\*80 dot matrix



- Supports 15 command modes included EPSON etc.
- Easy connectivity to a wide range of POS products.
- Power supply from 5V to 24V to prevent any mindless use of improper power input.
- OPOS/JPOS driver is standard.

### Ordering information:

LCD-50BU: 5" TFT monitor, with stand, black, USB( optional for RS232)

# LCD-50

## TFT-LCD Customer Display

### Specification

General	Display Method	TFT-LCD Display(5 inch COLOR PANEL)
	Number of characters	40 character(20columns×2line) 80 character(20columns×4line)
	Brightness	>350cd/m2
	Resolution	480*272 or 800*480
	Character font	24*48/40*80 dot matrix
	Character type	95 Alphanumeric, 32 international characters
	Character size	8(H)×5.25(W)mm
	Dot size (X×Y)	0.23×0.23mm
	Panel Dimension	113.5 (L) mm×65.5 (W) ×40 (H)
	Pole Dimension	Per support length : 163 (L) ×27.65 (DIA) mm/ 80 (L) ×27.65 (DIA) mm
	Base Dimension	126 (L) ×89 (W) ×13.5 (H) mm
	Viewing Angle	Max. 135°
	Horizontal Rotation	Max. 355°
	Weight	600grams
Commands Mode		15 kinds, E. g LD220, ESC/POS, AEDEX, UTC/S, UTC/P, ADM788, DSP800, CD5220, EMAX, LOGIC CONTROL etc
Language Support		CF437, KATAKANA, CP850, CP860, CP863, CP865, WCP1252, CP857, WCP1250, WCP1253, WCP1255, WCP1251, CP866, CP852, CP737, CP858, CP864, WCP1257, WCP1258
Interface		RS-232 (serial) /USB
Connection	Baud rate	Direct connection 9600/19200/38400/57600/115200 bps
Reliability	MTBF	30000 hours
Power	Consumption	5-24 VDC
Safety	EMC standards Safety standards	FCC, CE, ROHS



Birch is a trademark of Birch Technology INC.

All other products, brands or companies are trademarks or registered trademarks of their respective companies.

Specifications are subject to change without prior notice

BIRCH TECHNOLOGY INC 7F-13, No79, Hsin Tai 5th Rd., Sec 1, Hsichih Dist., New Taipei City, Taiwan Tel:886-2-2698-9596 Fax:886-2-2698-9537

E-mail:sales@mail.birch.com.tw <http://www.e-birch.com> <http://www.birch.com.tw/>

