

# SuperLead

苏州斯普锐智能系统有限公司

## 7350

立式二维码扫描小平台 (百万像素)  
Presentation Scanner (Megapixels)



大视野

Large Field of View



情感化设计  
Emotional Design

- 物体自感应
- 内置RS232和USB接口
- Object self induction
- Build in RS232 and USB interface
- 超大扫描窗口
- 三种工作模式 (普通模式、手机屏模式、快速移动模式)
- Super large reading window
- 3 working modes (normal mode, mobile phone screen mode and fast moving mode)

**Physical Characteristics**

尺寸Dimensions:	150mm x 95mm x 98mm
重量Weight:	295g
电压Voltage:	5 VDC $\pm$ 10 %
电流Current:	500mA (Operating)

**Performance Characteristics**

光源Light Source:	Illumination: 617nm RED LED
视场角Field of View:	55° (H) x 47° (V)
偏转/倾斜/旋转Roll / Pitch / Yaw:	360°, $\pm$ 65°, $\pm$ 60°
打印对比度Print Contrast:	15% minimum reflective difference
可识别电子屏幕Screen Intensity :	30% 及以上
运动容差Motion Tolerances	up to 200 cm per second
接口支持Interfaces Supported:	USB, RS232
传感器像素Image (Pixels) :	1280 pixels (H) x 1080pixels (V)

**Symbology Decode Capability**

一维条码1-D:	UPC, EAN, Code128, Code 39, Code 93, Code11, Matrix 2 of 5, Interleaved 2 of 5, Codabar, etc.
二维条码2-D:	PDF417, Data Matrix, Maxicode, QR Code, Aztec, etc.
条码精度Minimum Resolution	3 mil Code39

**User Environment**

工作温度Operating Temperature:	0°C to 50°C
存储温度Storage Temperature:	-40°C to 70°C
湿度Humidity:	0% to 95% relative humidity, non-condensing
抗跌落 Drop Specifications:	Designed to withstand 1m drops
环境光免疫Ambient Light Immunity:	100,000 Lux.

**Decode Ranges**

3.13mil C39	30mm-50mm
4.7mil C39	30mm-80mm
5.13mil C39	20mm-115mm
6.88mil PDF	0mm-160mm
10mil DM	10mm-180mm
20mil QR	0mm-230mm

Performance may be impacted by bar code quality and environmental conditions

