



## SURPASS SERIES - Desktop Direct Thermal Label Printer

4" Wide GS-2408D

POWERFUL, HIGH PERFORMANCE, AFFORDABLE



### KEY FEATURES

- 203.2mm (8") per second print speed for 203 DPI.
- 400 MHz 32-bit ARM9 processor with 64 MB SDRAM, 32 MB Flash memory or 64 MB SDRAM, 128 MB Flash memory.
- Internally scalable true type font engine.
- USB Host for scanner or PC keyboard.
- Firmware emulates EPL, ZPL, ZPL II, DPL, TSPL.
- BarTender Free Windows® drivers and label design software (available via download).
- Provide Windows printer utility, Windows SDK and Android SDK.
- Solution for retail POS, shelf labeling, office application, shipping.

# SURPASS SERIES -

## 4" Desktop Direct Thermal Label Printer



PRINTER MODEL	GS-2408D	GS-3405D
Level	Economic	Economic
Resolution	8dots/mm (203DPI)	12dots/mm (300DPI)
Printing Method	Direct Thermal	
Max. print speed	203.2mm (8")/second	127mm (5")/second
Max. print width	104mm (4.1")	108.4mm (4.27")
Max. print length	2,794mm (110")	1,016mm (40")
CPU	400MHZ, 32-bits, ARM9	
Memory RAM	64MB SDRAM	
Memory ROM	32MB Flash Memory	128MB Flash Memory Option
Interface	USB 2.0 High Speed 480Mbps USB Host 2.0, for scanner or PC keyboard Internal Ethernet 10/100Mbps Internal Bluetooth 4.0 (factory option) Internal Wi-Fi (factory option)	
Real Time Clock	N/A	
Buzzer	N/A	
Dealer options	N/A	
Sensors	Head open sensor, Reflective sensor (moveable), Transmissive sensor (moveable)	
Power	External universal switching power supply Input: AC 100-240V, 2.5A, 50-60Hz, Output: DC 24V, 2.5A, 60W	
User Interface	1 power switch, 2 buttons (Feed & Pause), 2 LEDs (Online, Error)	
Internal fonts	8 alpha-numeric bitmap fonts True type font engine (need download scalable font file)	
1D Barcode	Code 11, Code 39, Code 93, Code 128 (subsets A, B, C), UPC-A, UPC-E, UCC-128, Codabar, EAN/JAN-8, EAN/JAN-13, Interleaved 2 of 5, ITF14, MSI Plessey, PostCode, Telepen	
2D Barcode	QR Code, Micro QR Code, PDF417, Micro PDF417, Grid Matrix, MaxiCode, Aztec Code, Data Matrix	
Rotation	Font and barcode support 0, 90, 180, 270 degree	
Printer language	Compatible to EPL, ZPL, ZPL II, DPL, TSPL	
Media type	Continuous, die-cut, black mark, fan-fold, notched (outside wound)	
Media width	15~112mm (0.6"~4.4")	
Media thickness	0.055~0.254mm (2.17~10mil)	
Media core diameter	25.4mm (1")	
Label roll capacity	127mm (5")OD	
Label length	5~2,794mm (0.2"~110")	5~1,016mm (0.2"~40")
Physical dimension	180mm(W)x174.7mm(H)x238mm(D)	
Weight	1.76kg	

### Enclosure

ABS plastic

### Certification

FCC, CE, CCC, BIS, CB

### Environment condition

Operation: 5~40°C, 25~85% non-condensing  
 Storage: -40~60°C, 10~90% non-condensing

### Environment concern

Comply with RoHS, REACH, WEEE

### Accessories

Windows labeling software CD disk/Quick start guide/USB cable/Power cord External universal switching power supply

### Limited warranty

Printer: 2 years  
 Print head: 25km (1 million inches)/12 months  
 Roller: 50km (2 million inches)/12 months

### User options

External roll mount

### GAINSCHA GROUP TECHNOLOGY COMPANY

Add: 6/F, No.168 Yile Road, Pingsha Town, Jinwan district,  
 519055 Zhuhai, China  
[www.gainscha.com](http://www.gainscha.com)

### GAINSCHA NETWORK INC.

Add: 1104 Huarong Building, 9 Xing Ao Road, Hengqin New Area,  
 Zhuhai, 519031, Guangdong, China

### GAINSCHA INTERNATIONAL(SHENZHEN)CO, LIMITED

Add: A704-B, Huazhong University of Science and Technology,  
 No. 9 Yuexing 3th Road, Gaoxin District, Yuehai Street,  
 Nanshan District, Shenzhen

Tel : +86 756 3965698  
 Fax : +86 756 3965694  
 E-mail : [sales@gainscha.com](mailto:sales@gainscha.com)  
 Website: [gainscha.com.tw](http://gainscha.com.tw) | [gainscha.com](http://gainscha.com)